



SIZE :

120×120×38mm

CONSTRUCTION :

- Die-cast aluminum housing
- Glass fiber reinforced plastic impeller, UL 94V-0 rating
- Impedance protected
- Leader wire or terminal is available

OPERATING TEMPERATURE :

Ball Bearing -30°C to +75°C

Sleeve Bearing -10°C to +70°C

WEIGHT :

530 grams

Specifications

Specifications are subject to change without notice

MODEL	BEARING	RATING VOLTAGE	FREQUENCY	RATING CURRENT	POWER CONSUMPTION	SPEED	AIR FLOW		STATIC PRESSURE	NOISE
		VAC	Hz	A	W	RPM	m ³ /min	CFM	mmH ₂ O	dB-A
FA12038HA1 FA12038HA1	Ball Sleeve	110/120	50/60	0.22/0.18	21/18	2650/2950	2.58/3.20	91/113	6.35/7.62	40/45
FA12038HA2 FA12038HA2	Ball Sleeve	220/240	50/60	0.14/0.12	22/21	2700/3100	2.68/3.25	95/115	8.38/9.65	42/47
FA12038MA2 FA12038MA2	Ball Sleeve	220/240	50/60	0.12/0.11	20/19	2600/2950	2.58/3.20	91/113	6.35/7.62	40/45
FA12038LA2 FA12038LA2	Ball Sleeve	220/240	50/60	0.09/0.08	16/15	2200/2500	2.03/2.25	72/80	3.56/5.33	37/39
FA12038HA3 FA12038HA3	Ball Sleeve	380	50	0.06	18	2600	2.58	91	6.35	40

